



TVU PowerPac and TVU PowerPac 2 Batteries

Advantages

- △ Compact, Lightweight and Ultra-Portable
- △ 4 level indicator light helps avoid power disruptions
- △ D-tap and USB output powers mobiles, cameras and other devices
- △ Compatible with all standard V-mount system
- △ No memory effect

The most proficient, high capacity, light-weight and compact V- mount batteries.



Features of TVU PowerPac and TVU PowerPac 2 Batteries

Light weight and compact

Smallest V Lock Battery, can be held in one hand. Perfect for outdoor shoots

OLED Screen

4 level indicator light helps understand battery voltage and capacity

D -tap and USB output

Supply power to not only cameras but mobile phones, laptops, power lights and many other devices.

Intelligent control

Intelligent control protection from- over heating, over charging, over discharge and over current

Rechargeable

Rechargeable Li- Ion battery with adaptor

No Memory Effect

Other batteries if recharged repeatedly after being only partially discharged, gradually lose usable capacity owing to a reduced working voltage. No such memory effect happens with TVU PowerPac and TVU PowerPac2

TVU PowerPac Technical Specifications

Model

TVU PowerPac



Mounting

V Mount

USB-C Input/ Output

5V/3A 9V/3A 12V/3A 15V/3A 20V/2.2A

Weight

310g

Capacity

14.8V 6.8 Ah 50 Wh

Support

PD2.0, QC2.0, QC3.0, FCP, BC1.2 and other fast charge protocols

Working temperature

-20 Degree Celsius to approx. +55 Degree Celsius

D-TAP Output

14.8V/8A(MAX)

Micro USB Input

5V/3A

Applicable charger

16.8V/2A Charger, cellphone adapter, other adapters supporting PD2.0 fast charge protocols

USB-A Output

5V/2.4A 9V/2A 12V/1.5A

Dimensions

100(L)mm x 71(W)mm x35(H)mm

Support

QC2.0, QC3.0, FCP, BC1.2 and other fast charge protocols

Model

TVU PowerPac 2



Mounting

V Mount

USB-C Input/ Output

5V/3A 9V/3A 12V/3A 15V/3A 20V/2.2A

Weight

520g

Capacity

14.8V 6.8 Ah 98 Wh

Support

PD2.0, QC2.0, QC3.0, FCP, BC1.2 and other fast charge protocols

Working temperature

-20 Degree Celsius to approx. +55 Degree Celsius

D-TAP Output

14.8V/10A(MAX)

Micro USB Input

5V/3A

Applicable charger

16.8V/2A charger, cellphone adapter, other adapters supporting PD2.0 fast charge protocols

USB-A Output

5V/2.4A 9V/2A 12V/1.5A

Dimensions

101(L)mm x 72(W)mm x54.5(H)mm

Support

QC2.0, QC3.0, FCP, BC1.2 and other fast charge protocols



www.tvunetworks.com
 857 Maude Avenue, Mountain View, CA, 94043
 + 1.650.969.6732