

TVU One®

Advantages

- △ Reliably transmits high picture quality video even in congested
- △ or challenging environments
- △ Uses patented IS+ transmission algorithm
- △ Support for HDR and 1080P60 encoding at as little as 800kbps
- △ Long internal battery life
- △ HEVC/H.265 video compression
- △ CNCed from high-density aluminum

Unlike any transmitter.

HD picture quality with half-second latency at 3Mbps.



TVU One® - TM1000 V3 Technical Specifications*

Video Input

3G-SDI and HDMI 2.0 video inputs

Audio Input

Up to 8 channel embedded SDI/HDMI audio

Supported Data Connections

Simultaneously aggregate up to 12 data connections including internal/external cellular, WiFi, Ethernet, IP Microwave or Satellite (Ka/Ku/BGAN). System includes up to 6 embedded CAT12 3G/4G/LTE modems (WCDMA B1,2,4,5,6,8,9,19 LTE B1,2,3,4,5,7,8,9,12,13, 18,19,20,26,28,29,30,32,41,42,43,48,66) and optional 5G modems, embedded 2.4/5GHz WiFi, Ethernet, and 4 USB connections for external modem connections

Modem Support

6 embedded 4 USB

Power Source

A single removable, rechargeable internal battery with an optional external Gold or V-Mount battery

Transmitter Controls

One button power-on, on board monitoring and management, remote monitoring and management using mobile smart device or Command Center web service

Power Consumption

Max 30W

Storage

Up to 18 hours with 128 SD card

Video Input Resolution

SDI Input

HD 1080p 25/29.97/30/50/59.94/60, 1080i 50/59.94/60, 720p 50/59.94/60 SD PAL 625i/50 SD NTSC 525i/59.94 HDMI Input

HD 1080p 25/29.97/30/50/59.94/60, 1080i 50/59.94/60, 720p 50/59.94/60 SD PAL 625i/50

SD NTSC 525i/59.94

Encoding and Compression Standard

H.265/HEVC or H.264

Variable Bit-Rate Encoding

TVU Smart VBR hardware encoder

Bit-Rate

100K-30Mbps

Return Video Feed

TVU One feed or SDI input at Server HotSpot stream on the same server

Recording

Supported, Dual Encoder

Glass-to-Glass Latency

0.5 seconds

Battery Run Times

Internal - 4.5 hours External (PowerPac) - 8 hours

SD Card Slot (up to 256G)

1 card slot

Operating Temperatures

0°C to 40°C (32°F to 104°F)

Unit Dimensions & Weight

7.48 x 4.72 x 2.76in (190 x 120 x 70mm) 2.2lbs (1kg)

Voice Communication

Bidirectional IFB

Color Space & Bit-depth

8bit/10-bit, 4:2:0

Patented Transmission Algorithm

Inverse Statmux Plus (IS+)

Start-Up Time

Less than 30 seconds

External Interface Connections

SDI, HDMI, USB, Ethernet, IFB

Store and Forward Supported

DC Input

Right angle Mini Jack DC input that connects to external battery or supplied AC adapter. External power adapter: 11-19V DC

Control Screen Specifications

3.5 inch, 16:10 LCD touchscreen

FCC and CE Compliant

Anatel Certified



www.tvunetworks.com 857 Maude Avenue, Mountain View, CA, 94043 + 1.650.969.6732

TVU One® Software Packages

| Features | Standard | Pro | Enterprise |
|--|----------|-----|------------|
| One Button Operation | Yes | Yes | Yes |
| 30 Second Start Up | Yes | Yes | Yes |
| Encoding: H.265/HEVC or H.264 | Yes | Yes | Yes |
| Hotspot Monitoring and Control | Yes | Yes | Yes |
| Inverse StatMux Plus (IS+) | Yes | Yes | Yes |
| Live Video Transmission | Yes | Yes | Yes |
| Live Record Hours | 0.5 | 3.5 | 7 |
| Smart VBR | Yes | Yes | Yes |
| Web Interface Control | Yes | Yes | Yes |
| Satellite/Cellular Hybrid Connectivity | Yes | Yes | Yes |
| Economy Preview | No | Yes | Yes |
| 4-Channel Audio | No | Yes | Yes |
| TVU Voice (VoIP/IFB) | No | Yes | Yes |
| Accelerated File Transfer | No | Yes | Yes |
| Time Code Marking | No | Yes | Yes |
| External USB Modem Support | No | Yes | Yes |
| Encoding Switching: H265 & H264/H265 | No | Yes | Yes |
| Progressive Download | No | No | Yes |
| Hotspot Aggregated High Speed Internet Access | No | No | Yes |
| Metadata Marking | No | No | Yes |
| Video Clipping and Download | No | No | Yes |
| Return Video Feed | No | No | Yes |
| Dual Encoding | No | No | Yes |
| GPS Tracking | No | No | Yes |
| Data Priortization Control | No | No | Yes |
| TVU Router: High speed wireless connectivity anywhere | No | No | Yes |
| TVU Timelock: Untethered multiple synchronized remote transmission | No | No | Yes |
| Number of Enabled USB External Modem/Dongle Ports | 0 | 2 | 4 |
| TVU Application Compatibility | | | |
| TVU Alert: Instant alert messaging across all TVU devices | Yes | Yes | Yes |
| TVU Analytics: Dashboard monitoring of all data usage | Yes | Yes | Yes |
| TVU Grid: IP video switching, routing and distribution | Yes | Yes | Yes |
| TVU MediaMind: AI & cloud based story centric workflow platform | Yes | Yes | Yes |
| TVU Producer: Cloud based feature rich multicamera production | Yes | Yes | Yes |
| TVU Booking: Automated management of all TVU transmissions | No | No | Yes |



857 Maude Avenue, Mountain View, CA, 94043 + 1 650 969 6732